

# WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

51) International Patent Classification $^6$ :  G01V	A2	(11) International Publication Number: WO 97/06452
21) International Application Number: PCT/US 22) International Filing Date: 29 July 1996 ( 30) Priority Data: 60/001,802 2 August 1995 (02.08.95) 60/006,312 7 August 1995 (07.08.95) 71) Applicant (for all designated States except US): H COUSTICS, INC. [US/US]; 999 Lehigh Station R Box 23447, Rochester, NY 14692 (US).  72) Inventor; and 75) Inventor/Applicant (for US only): BOUYOUCOS, [US/US]; 1 Stonegate Lane, Pittsford, NY 14534  74) Agent: LUKACHER, Martin; Suite 900, Clinton Rochester, NY 14604 (US).	(29.07.9 (29.07.9 (15) (15) (15) (15) (15) (15) (15)	CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).  Published  Without international search report and to be republished upon receipt of that report.

#### (57) Abstract

An array system, which provides a unipolar acoustic impulse with a broad spectral response underwater, utilizes a vertical array of air gun or electric spark sources whose individual peak source strengths are essentially constant over the array length, but whose individual source periods vary with depth. The array of sources produces in each instance a near-unipolar, impulsive signature with a broad pedestal-like spectrum. The system may be used for underwater object location and also for seismic exploration.

## FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgystan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic	SD	Sudan
CF	Central African Republic		of Korea	SE	Sweden
CG	Congo	KR	Republic of Korea	SG	
CH	Switzerland	KZ	Kazakhstan	SI	Singapore
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovenia
CM	Cameroon	LK	Sri Lanka		Slovakia
CN	China	LR	Liberia	SN	Senegal
CS	Czechoslovakia	LT	Lithuania	SZ	Swaziland
CZ	Czech Republic	LU	Luxembourg	TD	Chad
DE	Germany	LV	Latvia	TG	Togo
DK	Denmark	MC	Monaco	TJ	Tajikistan
· EE	Estonia	MD	· · · · · · · ·	TT	Trinidad and Tobago
ES	Spain		Republic of Moldova	UA	Ukraine
FI	Finland	MG	Madagascar	UG	Uganda
FR	France	ML	Mali	US	United States of America
GA		MN	Mongolia	UZ	Uzbekistan
UA	Gabon	MR	Mauritania	VN	Viet Nam

-1-

# SYSTEM FOR GENERATING AND TRANSMITTING ACOUSTIC SIGNALS UNDERWATER

This application claims the priority benefit of pending U.S. provisional application Serial Nos. 60/001,802 filed August 2, 1995; 60/001,947 filed August 7, 1995 and 60/006,312 filed November 7, 1995.

### DESCRIPTION

The present invention relates to systems for generating acoustic or seismic signals in underwater environments, and particularly to air gun acoustic signal generating and transmitting arrays.

Air guns are well known in the field of marine seismic exploration. Such guns are commonly formed into large horizontal arrays that are streamed from a tow vessel at a fixed depth of 15 feet or so. Such arrays are used for projecting a coherent, time-aligned impulsive signal, of high energy content and broad spectral bandwidth, downwardly into the earth for the delineation of oil bearing strata.

The acoustic signature of typical air guns, such as shown in Harrison, U.S. Pats. 4,623,033 of November 18, 1986 and/or 5,654,493 of November 15, 1994, mounted near a water-air interface with the measurement made in the far field below the gun, consists of an impulsive event followed by a rapidly decaying wave train, as illustrated in Figures 1 A & B. The positive-going impulse, produced by the explosive release of compressed gas, is quickly followed by a mirror-like negative impulse arising from the pressure-release surface reflection. This impulsive-pair is followed by a decaying oscillatory tail which arises from the resonant, decaying oscillation of the residual gas bubble.

15

20

The resonant frequency of this gas bubble oscillation is given by:

$$f_c = \frac{55(14.7 + 0.444d)^{5/6}}{(P_c.V_c)^{1/3}}$$

where:

 $f_c$  = Bubble resonant frequency (Hz)

d = Depth in feet

 $P_c = Gun cavity pressure$ 

 $V_c$  = Charge cavity volume

(See FIG. 2.)

15

20

The spectrum of the event, also depicted in FIG. 1B, consists of a relatively narrow spectral peak associated with the fundamental bubble resonant frequency followed by lower level harmonic contributions.

This spectrum by itself is inadequate to yield the resolution required for seismic exploration. Accordingly, investigators in the field have developed long arrays of air guns with each gun (or gun group) having a different volume of compressed air so as to distribute the resonant frequencies of the guns over a wide frequency range. The peaks and valleys of the spectra of the multiplicity of guns are then distributed by design to help flatten the composite spectrum of the array of guns. Since guns of different volumes have different spectral levels, groups of guns are incorporated to establish the final flattened spectrum. This flattened spectrum is associated with a singular impulse cycle, as shown in Figs. 3 A & B, and becomes useful for broadband high resolution geophysical prospecting.

Reference may be had to the following U.S. Patents for information concerning such horizontal arrays: Huizer, 4,727,956 of Mar. 1, 1988; Williams, 4,955,952 of Sept. 11, 1990; French, 4,254,480 of Mar. 3, 1981; Ray, 4,441,174 of Apr. 3, 1984; Brock, 3,437,170 of Apr. 8, 1969; Mott-Smith, 3,893,539 of July 8, 1975; White, 4,372,420 of Feb. 8, 1983; Ruehle, 4,382,486 of May 10, 1983; Ongkiehong, 4,486,864

- 3 -

of Dec. 4, 1984; Desler, 4,718,045 of Jan. 5, 1988; Dunbar, 4,868,793 of Sept. 19, 1989; Garrotta, 4,914,636 of Apr. 3, 1990; and Duren, 5,281,773 of Jan. 25, 1994.

In the field of underwater detection of submerged objects at long horizontal ranges in a deep water column, it has been found useful to deploy a vertical line array of sources, long enough to possess vertical directivity to assist in the delineation of the submerged object from surface and bottom reflections (reverberation).

It has been discovered, in accordance with the invention, that one can use a vertical line array of air guns for the purpose of flattening the spectrum and that, instead of requiring a distribution of air gun volumes to distribute the resonant frequencies of the individual guns as is done in horizontal arrays for seismic exploration, the desired distribution of resonances can be obtained from the distribution in depth of guns of the same or essentially similar volumes.

It has further been found through model studies and measurements that the peak output of a properly designed air gun of a given, fixed volume is relatively constant over a sizable depth range (e.g., 100 to 400 feet), even though its bubble resonant frequency varies with depth. As stated above, air guns of different volumes (all at the same supply pressure and depth) will exhibit not only different resonant frequencies, but also different peak outputs.

Accordingly, a key feature of the invention is that a vertical array of air guns of constant or similar volume will provide an array of constant peak amplitude sources. This simplifies and aids in the array design for control of beam patterns, especially in the high frequency regime where the contribution of bubble resonances is reduced and the primary output arises from the initial impulse event. In arrays with guns with a distribution of volumes, design of the array is more difficult than with constant volume guns, since the design is complicated by the need to compensate for small volume guns which have less output then large volume guns. In addition, such groups of smaller guns lead to additional complexity, increased mounting and air connection hardware, and increased drag. This may not be a particular problem for horizontal arrays, since more horsepower can be used by the tow ship for maintaining a desired speed and rate of area coverage. However, for a vertical array, such additional complexity and

15

20

25

10

15

20

25

resultant drag creates increased array tilt. For uniform azimuthal search the array cannot be deformed appreciably from the vertical. Thus such complexity tends to compromise search rate, and may require correction as by the addition of cumbersome dead weight at the bottom of the array which can add significantly to the size and cost of the array handling system.

In summary, the invention is based upon the discovery that vertical arrays containing air guns having identical or similar air volumes can exhibit essentially constant peak output as a function of depth while, at the same time, having a bubble resonance that is a function of depth, increasing as depth increases. The constant peak output contributes to a beam pattern at the higher frequencies that is symmetrical about an axis normal to the vertical axis of the array. At the lower frequencies, the bubble resonance distribution for an array of constant volume guns creates a broad, flat pedestal which is elevated some 5 to 6 dB above the higher frequency output. This broadband pedestal energy is useful for object detection and localization at extended ranges, and its flat spectrum is beneficial for high range resolution and for the suppression of clutter.

In a preferred embodiment, a vertical array of equal or similar size air guns provide a transmitted signal on axis that is characterized by a singular broadband, impulsive event and with a spectrum which exhibits a broad pedestal-like response. The oscillatory nature of the signature and spectrum of any individual gun is smoothed in the array by the spreading of the periods of these individual gun signatures due to the dependance of such signature periods on depth (on ambient pressure).

Further in accordance with the invention two or more vertical arrays of air guns, each array comprised of guns of fixed volume, with the volume being different for each array, exhibit pedestals that have different frequency bands. For a given, common depth range, such arrays may be merged to yield a composite spectrum which exhibits a constant flat level, broader in frequency bandwidth than for any of the individual arrays, and which can have a smooth joint at the junction of the several bands.

10

15

It has been found, in accordance with another aspect of this invention, that electrically controlled underwater spark discharge sources exhibit characteristics similar to air guns.

FIGS. 12 and 13 show the character of an underwater spark discharge and its spectrum at a depth of 188 feet. The total event consists of two (or more) impulses separated by a relatively long rarefaction interval.

The initial spike-like event is associated with the impulsive formation of a steam cavity as a result of the heat energy introduced in to the medium by the electric discharge. The steam cavity grows in size and eventually collapses to create the second impulse event. The steam condenses to form water during the collapse cycle, and the event-pair may be the characteristic signature.

The spectrum of the event-pair signatures is shown in FIG 13. This spectrum has a relatively broad main lobe followed by a decaying succession of narrower lobes.

The period,  $\tau$ , in seconds between the main impulse events is given by the expression below where  $\rho$  is the density of the water in kilograms per cubic meter; E in energy in Joules, and  $P_{ave}$  is the average ambient pressure of the water acting on the source in Pascals.

$$\tau = 1.83 \left(\frac{3}{4\pi}\right)^{\frac{1}{3}} \rho^{\frac{1}{2}} \left(\frac{E^{\frac{1}{3}}}{P_{ave}^{\frac{5}{6}}}\right)$$

This period is proportional to the one-third power of the discharge energy, and is inversely proportional to the 5/6 power of the ambient pressure.

Accordingly, a vertical array of sparker electrodes, fired simultaneously with roughly equal energies, will appear as an array of events with dispersed periods, creating a broadened spectrum as has been shown with the air guns.

In accordance with this object of the invention, it has been found that a plurality of electric spark discharge units (also known as sparkers) may be arranged in a vertical

line array for the purpose of flattening the spectrum of the acoustic or seismic signal produced by the array and that, instead of requiring a distribution of sparkers operating at different energies, the desired distribution of impulse events can be obtained from the distribution in depth of the sparkers which provide the same or essentially similar energy spark discharges.

Accordingly, a key feature of this aspect of the invention is to provide a system comprising a vertical array of sparkers, electrically controlled to produce underwater spark discharges of the same energy, or approximately like energy at selected depths to generate and transmit acoustic or seismic signals having a broad and essentially flat spectral response useful for object detection and localization at extended lateral ranges as well as for seismic exploration to project a coherent impulse signal of high energy content and broad spectral bandwidth downwardly into the earth for the delineation of oil bearing strata and other geo-physical characteristics.

The foregoing and other objects, features and advantages of the invention will become apparent from a reading of the foregoing and following description in connection with the accompanying drawing in which

FIGS. 1A and B are plots illustrating the acoustic time-signature and spectrum of an air gun at a 2- foot depth, including the effects of surface reflections;

FIG. 2 are plots of air bubble resonant frequency variation with depth for air 20 guns of different volumes;

FIGS. 3A and B are respectively plots of the impulse and frequency response of a prior art horizontal air gun array;

FIGS. 4A to D are plots of the waveform or time history of the signal from a single air gun at different depths;

FIGS. 5A D are plots of the spectral response of the signal generated by the gun at different depths;

FIGS. 6 is a plot comparing the measured energy spectrum of a 10 cubic inch air gun at 100 ft. depth with an analytical model prediction of that performance.

FIGS. 7A to D are plots illustrating the time history and spectral response of a vertical array of 46, 10 cubic inch air guns, in accordance with an example of the

15

20

25

invention. The plots of FIGS. 7A and 7B are based upon data which are exemplified in the plots of FIGS. 4 A-D and 5A-D. FIGS. 7B and 7C are from an analytical model of the vertical array of 10 cubic inch guns;

FIG. 8 is a schematic diagram of an interleaved compound vertical array of air guns having two sub-arrays of guns, each subarray consisting of guns of equal volume but with the volumes of the guns between the sur-arrays being different;

FIGS. 9A and B are plots of the time history and spectral response of the arrays shown in FIG. 8;

FIGS. 10A to F are beam patterns of the array shown in FIG. 8;

FIG. 11 is a schematic diagram of an acoustic or seismic signal generating and transmitting system incorporating a vertical array such as shown in FIG. 8, the system being in accordance with the present invention.

FIG. 12 is a plot showing the acoustic time signature of an exemplary underwater spark discharge event;

FIG. 13 is plot showing the power spectrum of the signature of FIG. 12;

FIGS. 14 and 15 are similar to FIGS. 4A and 4C, and respectively illustrate the signature of a 19KJ (kilo-Joule) spark discharge source or sparker at 100 and 276 feet below the water surface, respectively;

FIGS. 16 and 17 are similar to FIGS. 5A and 5C and show the spectra of the signatures of FIGS. 14 and 15;

FIG. 18 is a plot showing the time signature in the far field of a vertical array of sparkers as a composite pulse, the plot being for an array of 23 sparkers spaced 8 feet apart and extending over an depth range from 100 to 276 feet, with the time signature being defined in the far field at the mid-depth of the array, or at 188 feet;

FIG. 19 is a plot showing the spectrum of the impulse signature of FIG. 18;

FIGS. 20 and 21 are, respectively, plots of the signature and spectrum of another array, specifically an array of 46 sparkers extending over a length of 360 feet from a depth of 100 to 466 feet; and

FIG. 22 is a block diagram of a system according to the invention.

Referring to FIGS. 4A to D and 5A to D, the measured characteristics are illustrated for a 10 cubic inch gun of the type in the above referenced Harrison patents. The gun time-history and spectral characteristics are shown for selected depths of 100, 172, 244 and 316 feet. The time history (FIG. 4A-D) is characterized by a sharp impulse, tightly coupled in timing to the firing signal, followed by a decaying bubble oscillation whose frequency increases with increasing depth. The corresponding spectral characteristics of the shots of Figure 4A-D are illustrated in FIGS. 5A-D. As can be seen, the primary spectral peak moves from just above 50 Hz at 100 feet to just below 150 Hz at 316 feet. Thus, an adequately populated, vertically distributed array of such guns, in accordance with the invention, will exhibit a stagger-tuned, broadband spectral pedestal created by the sweep-out of the primary spectral peak as gun depth increases.

Referring to FIG. 6, the use of an analytical model in defining single gun performance is shown. Specifically FIG. 6 shows a broadband comparison of model prediction and measurement for the single 10 cubic inch gun at 100 foot depth. Agreement is good, at least out to 500 Hz.

FIG. 7A and B show the impulse time history and spectral response, respectively, projected for a vertical array of 46 10- cubic inch air guns, according to the invention, and based on single gun measurements. The agreement with an analytical model of this array is shown in FIG. 7C and D.

Gun-to-gun interactions are not included above. Such interactions for 10 cubic inch guns should be negligible for spacings larger than 5 feet or so, and may amount to a reduction of several dB in pedestal amplitude at spacings on the order of 2 to 3 feet.

Interaction measurements between guns made at depths of the order of 100 feet have shown that interacting clusters of, say, two to four guns at gun-to-gun spacings of approximately one to three feet can create unique spectral characteristics not evidenced by a single gun alone. Spaced vertical arrays of such gun clusters can then provide a flat, extended spectrum with a single impulse acoustic signature, but with the spectrum covering a different frequency band than is obtained if all the guns were spaced apart at non-interacting (or mildly interacting) distances.

15

20

25

- 9 -

An interleaved compound array is shown in Figure 8. This array is to provide a high source level transmission (which may be repeated to provide a rapid sequence of such shots) for long range, shallow water detection of moving objects and for the concomitant suppression of reverberation. The array consists of three subarrays that overlap and are interleaved. The first subarray is the LF or Low Frequency array comprised of 25-70 cubic inch guns covering roughly the 30 to 80 Hz frequency range (when the top of the array is at 100 feet submergence). This array is about 300 feet long. The second subarray is the MF or Mid Frequency array consisting of 75-10 cubic inch guns covering the 80 to 200 Hz range. It is also 300 feet long, but starts at 200 feet below the surface. The third array is the HF or High Frequency array which is placed over the center 100 feet of the interleaved array, and uses 48-20 cubic inch guns working in combination with the 24-10 cubic inch guns located in the same aperture.

The array as shown is useful for water depths in excess of 200 meters, where the lowest frequencies may be necessary. An array may also be constructed out of 50 to 100 foot segments of the array of Figure 8, with such shorter apertures of low and/or high frequency capability individually deployed in water depths of 100 meters plus or minus to meet specific propagation characteristics.

The array of Figure 8 is also adequately populated so that it can be fired in a shaded distribution to excite single-mode propagation in ducted channels. In contrast with most other transduction technologies, an air gun not fired in an array acts as a rigid body and will have minimum interaction with guns selectively fired. This leads to wide flexibility in the array's application to special needs.

FIGS. 9A and B illustrate the interleaved LF and MF composite performance, based upon analytical modeling. The time waveform (FIG. 9A) is a single impulse, and the pedestal of the spectrum (FIG. 9B) extends from about 30 Hz to 220 Hz, gradually dropping off above that frequency. The overall transmission is characterized by a near-unipolar, impulsive signature with a flat pedestal-like spectrum. The notch at about 100 Hz is the joint between the 70 cubic inch LF array and the 10 cubic inch MF array. The architecture of the gun layout in the interleaved configuration provides the smooth transition between the LF and MF arrays. The HF array by itself provides a smooth

15

20

10

15

20

25

30

spectrum above 200 Hz not unlike that shown in FiGS. 9A and B, but the shorter array length is necessary for reasonable vertical beam widths at the higher frequencies.

Beam patterns from the analytical model are shown in FIGS. 10A-F for the interleaved (LF and MF) array (FIGS. 10A-C) and the high frequency (HF) array only (FIGS. 10D-F). The plots show band energy levels as a function of vertical angle for the frequency bands identified in the box in each of FIGS. 10A-F.

In the case of the LF and MF arrays the pedestal is dominating the output, and the stagger-tuning along the vertical line leads to asymmetry in the vertical beam patterns, with an effective upward tilt of the main response by about 7 degrees. This can be corrected by beam steering. The HF array operates above the pedestal region, and the patterns are more symmetrical. The main axis band energy levels differ by only 5 dB or so from the lowest (50 - 100 Hz) to the highest (400 - 500 Hz) band.

By firing the complete array repetitively with a timed sequence of shots spaced, say, at about 1 second intervals, the total band energy can be increased by 10 log N where N is the number of shots in the sequence. In this manner an increased total energy can be placed on the object to be detected and signal processing can properly collect the reflected energy in the sequence of returns to increase signal-to-noise ratios. Signal processing can also take advantage of the sequence of shots to distinguish a moving object from stationary clutter or reverberation.

Although the prior description has focussed on a vertical array with transmissions launched generally in the horizontal plane, the vertical array may also be fired with its main beam at any angle of elevation or depression by controlling the timing of the individual firing events. In particular, the array can be fired "end-fire" to launch a directional, broad-band impulse vertically downward.

A system incorporating the invention including the power and control elements is shown in FIG. 11. Compressed air provided by compressor 12 driven by a motor (prime power) 10 is fed to gas storage bottles 14 that, in turn, feed the peak energy for the sequence of transmissions from the gun array 16. The gun array is, in turn, controlled by a master control 20 and a gun controller 18 that receives feed back from the timing coil of each gun and adaptively refines the timing accuracy of each shot.

WO 97/06452

- 11 -

PCT/US96/12404

The several subarrays may be controlled for firing off a sequence of shots used for target (velocity) detection and reverberation suppression. A typical compressor size (capacity) is 300 HP.

Referring to the aspect of the invention where the impulsive events are obtained from sparkers, it can be seen from FIGS. 14-17 that the period between the electric discharge event and the cavity collapse reduces with increasing depth and the frequency of the spectral peaks increases with increasing depth.

An array of such sparkers, distributed vertically and fired simultaneously will, accordingly, yield a large initial pulse followed by a sequence of smaller pulses distributed in time. The sequence of smaller pulses arises from the time-spaced distribution of cavity collapse events due to the distribution in depth of the sparker devices. If N is the number of events, the magnitude of the composite pulse on the axis normal to and bisecting the center of the array should be NA, where A is the amplitude of the individual sparker initial event. This is illustrated in Figure 7 for an array of 23 sparkers spaced 8 feet apart, and extending over the depth range from 100 to 276 feet.

The spectrum of the composite pulse is shown in FIG. 19. This spectrum is smoothed and broadened relative to the individual event spectrum shown in FIG. 13, and is increased substantially in magnitude.

The singular impulse event of FIG. 18 and its broadened spectrum of FIG. 19 creates an ideal broadband interrogation pulse for underwater object detection at long range.

FIG. 20 and 21 illustrate the results for a larger array. This array includes double the number of sparker units (46) and extends over a length of 360 feet (from 100 to 460 feet).

As can be seen in FIG. 20, the impulse is approximately doubled in amplitude and better defined, and the spectrum of FIG. 21 is raised in amplitude, especially at the high end, and broadened.

FIG. 22 is a block diagram of the system showing a high voltage DC generator 30 feeding an energy storage bank, which may be a bank of high-voltage capacitors.

10

20

15

The energy storage bank is connected, via individual high voltage switching circuits to the sparker electrodes distributed along the vertical array. The electrical pulses may be provided via the switching circuits substantially simultaneously to create a broadside acoustic transmission, or may be sequentially delayed in time to steer the main beam of the array up or down. The voltage may be in the range of, for example, 5 to 10KV. The interconnecting cables to the electrodes may each have a high voltage conductor and an integral ground return, or the ground return may pass through the seawater to a common connection.

Alternatively the energy storage bank and switching circuits may be configured underwater, and distributed along the array so as to provide a close connection between the source of energy and its point of release into the environment. Although this distributed configuration may lead to system complexity, its advantage may reside in improved timing of the individual discharge events which maybe important if focus resides on the higher frequency portions of the composite transmitted impulse spectrum.

The foregoing description of an exemplary system and of exemplary arrays should be taken as illustrative and not limiting upon the invention.

- 13 -

PCT/US96/12404

#### **CLAIMS:**

WO 97/06452

- 1. A system for generating and transmitting acoustic or seismic signals underwater which comprise of a vertical array of units providing acoustic impulse events, each providing events of approximately equal energy in timed relationship, said units being spaced from the surface of the water at selected depths, thereby creating a composite acoustic or seismic signal which is a singular impulse having a substantially flat spectral response over a given frequency range.
- 10 2. The system according to claim 1 wherein said units are air guns of equal or similar volume.
  - 3. The system according to claim 1 wherein said units are spark discharge units.

15

5


- 4. The system according to Claim 3 wherein said discharge energy of each of said units is approximately alike.
- 5. The system according to Claim 1 where said events which emanate from 20 said units occur approximately simultaneously.
  - 6. The system of Claim 3 said units are operated by voltage pulses of voltage in the range of 5 to 10 KV.
- 7. The method of generating acoustic signals underwater to provide generally horizontally directed transmissions of broad bandwidth impulse events, which comprises the steps of spacing a plurality of impulse sources selected from the group consisting of air guns and sparkers at selected depths in a vertical array, and firing said sources substantially simultaneously.

- 8. The method of Claim 6 wherein said firing step is carried out by releasing substantially equal volumes of compressed air or with electrical pulses of generally like energy.
- 9. A system for generating and transmitting acoustic signals under water which comprises a vertical array of spaced air guns for use in a body of water, each of said guns possessing a charge chamber of equal or similar volume for the storage of gas under high pressure, said volume of compressed gas in each of said guns being explosively releasable from the guns, upon the command of a control signal, to form a vertical array of gas-filed cavities, said explosive release resulting in an initial acoustic impulse from each gun followed by a rapidly decaying oscillatory pressure signal whose oscillatory frequency is related to the resonant frequency of the discharged gas volume in each of said cavities at their respective depths of discharge, said vertical array of cavities forming a stagger-tuned array of cavities whose decaying oscillations create a sensibly flat spectral pedestal extending in frequency from the resonant frequency of the uppermost cavity in the array to the resonant frequency of the lower-most cavity in the array.
- 10. The system according to claim 10, with said spacing of said air guns in said array being of such amount as to promote the independent, free oscillation of said cavities, without significant interaction therebetween, thereby to enhance the pedestal spectral amplitude as well as the total acoustic energy output of said vertical array.
- 11. An interleaved array comprising a plurality of independent vertical arrays of air guns adapted to be disposed in a body of water at different depths below the surface of the water, said independent vertical arrays each comprising a plurality of guns of equal or similar air volumes, and said volumes in each of said arrays being selected to provide pedestal responses covering distinct and different frequency bands, and the depths of the individual arrays of said interleaved array being arranged to create smooth amplitude joints between adjoining pedestals.

- 15 -


- 12. In a vertical array of closely spaced acoustic impulse sources selected from the group consisting of air guns and electric sparkers, the method for providing horizontally directed transmissions of broad bandwidth, impulsive events which comprises the step of firing off selected ones of said closely spaced sources to provide a shaded distribution of firing thereby selectively exciting single mode propagation in ducted channels.
- 13. The method of claim 12 in which the timing of the firings of the individual sources is simultaneous to launch the main beam of the array horizontally.
- 14. The method of claim 12 in which the timing of the firings of the individual sources has a progressive distribution to launch the main beam of the array in a directed angle from the horizontal.
- 15. The method of claim 12 in which the timing of the firings of the individual sources has a progressive distribution to launch the main beam of the array vertically downward.
- 16. A system for generating and transmitting acoustic or seismic signals underwater which is comprised of a vertical ARRAY of units providing controlled acoustic impulse-like events, each unit providing at least two consecutive events in a timed relationship, the spacing or timing between events for a given unit being dependent upon the local water depth, said units being positioned from the water surface at selected depths relating to their vertical spacing and the corresponding spacing or spacing of said events, thereby to create a composite acoustic or seismic signal which is substantially a singular impulse having a broad response over a given frequency range.


- 17. The system of Claim 16, wherein the first of said at least two consecutive events from each unit are in alignment to obtain prescribed timing for each unit of the array.
- 5 18. The system of Claim 17, wherein the second of said at least two consecutive events from each unit are in alignment to obtain said prescribed timing for each unit of the array.




ACOUSTIC OUTPUT FOR SINGLE AIR GUN AT 100 FT. DEPTH

2/17








52.6 BAR-M (P-P), P/B RATIO 64.4:1














Energy Density Spectrum Level dB re  $(1 \mu Pa)^{2*}$  sec/Hz at 1 m






8/17







# 11/17







FIG. 11










# 13/17






























# THIS PAGE BLANK (USPTO)

\_\_\_\_\_



# WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



# INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classificati n 6:

G01V 1/02, 1/04, 1/157,
G01S 15/00

(11) International Publication Number: WO 97/06452

(43) International Publication Date: 20 February 1997 (20.02.97)

(21) International Application Number: PCT/US96/12404

(22) International Filing Date: 29 July 1996 (29.07.96)

(30) Priority Data: 60/001,802 2 August 1995 (02.08.95) US 60/001,947 7 August 1995 (07.08.95) US 60/006,312 7 November 1995 (07.11.95) US

(71) Applicant (for all designated States except US): HYDROA-COUSTICS, INC. [US/US]; 999 Lehigh Station Road, P.O. Box 23447, Rochester, NY 14692 (US).

(72) Inventor; and

(75) Inventor/Applicant (for US only): BOUYOUCOS, John, V. [US/US]; 1 Stonegate Lane, Pittsford, NY 14534 (US).

(74) Agent: LUKACHER, Martin; Suite 900, Clinton Square, Rochester, NY 14604 (US).


(81) Designated States: AL, AM, AT, AU, AZ, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).

#### Published

With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(88) Date of publication of the international search report: 10 April 1997 (10.04.97)

(54) Title: SYSTEM FOR GENERATING AND TRANSMITTING ACOUSTIC SIGNALS UNDERWATER



### (57) Abstract

An array system, which provides a unipolar acoustic impulse with a broad spectral response underwater, utilizes a vertical array of air gun or electric spark sources whose individual peak source strengths are essentially constant over the array length, but whose individual source periods vary with depth. The array f sources produces in each instance a near-unipolar, impulsive signature with a broad pedestal-like spectrum. The system may be used for underwater object location and also for seismic exploration.

# FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Стресе	NL.	Netherlands
BE	Belgium	HU	Hungary	NO	
BF	Burkina Faso	IE	Ireland	NZ NZ	Norway
BG	Bulgaria	IT	Italy	NZ PL	New Zealand
BJ	Benin	JP	Japan	PT	Poland
BR	Brazil	KE	Kenya		Portugal
BY	Belarus	KG	Kyrgystan	RO	Romania
CA	Canada	KP	Democratic People's Republic	RU	Russian Federation
CF	Central African Republic		of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
СН	Switzerland	KZ	Kazakhstan	SG	Singapore
CI	Côte d'Ivoire	L	Liechtenstein	SI	Slovenia
CM	Cameroon	LK	Sri Lanka	SK	Slovakia
CN	China	LR		SN	Senegal
CS	Czechoslovakia	LR	Liberia	SZ	Swaziland
CZ	Czech Republic	LU	Lithuania	TD	Chad
DE	Germany	LV	Luxembourg	TG	Togo
DΚ	Denmark	MC	Latvia	TJ	Tajikistan
EE	Estonia		Monaco	TT	Trinidad and Tobago
ES	Spain	MD	Republic of Moldova	UA	Ukraine
71	Finland	MG	Madagascar	UG	Uganda
R		ML	Mali	US	United States of America
GA	France	MN	Mongolia	UZ	Uzbekistan
3 A	Gabon	MR	Mauritania	VN	Viet Nam

### INTERNATIONAL SEARCH REPORT

International application No.
PCT/US96/12404

A. CLASSIFICATION OF SUBJECT MATTER  IPC(6) :G01V 1/02, 1/04, 1/157; G01S 15/00  US CL : 367/144, 147, 153, 154					
4	to International Patent Classification (IPC) or to bot	h national classification and IPC			
<del></del>	LDS SEARCHED				
Minimum	documentation searched (classification system follow	ed by classification symbols)			
U.S. :					
Documenta none	ation searched other than minimum documentation to the	he extent that such documents are included	in the fields searched		
	data base consulted during the international search (n RBIT database; files inspec, wpat, ntis	name of data base and, where practicable	, search terms used)		
C. DOC	CUMENTS CONSIDERED TO BE RELEVANT				
Category*	Citation of document, with indication, where a	ppropriate, of the relevant passages	Relevant to claim No.		
X, P	US, A, 5,535,176 (YANG) 09 Ju 22-60.	uly 1996, column 2, lines	1, 5, 16, 17, 18		
X	US, A, 4,497,044 (SILVERMAN) 2 column 11, lines 50-65 and column	1, 2, 5, 16, 17, .18			
Y	US, A, 4,254,480 (FRENCH) 03 March 1981, column 10, 3, 4, 6 line 61-column 11, line 40.				
Y	US, A, 4,170,002 (STRANGE) 02 October 1979, entire 7, 8 and 12-15 document.				
Y	US, A, 4,721,180 (HAUGHLANI 1988, entire document.	D ET AL.) 26 JANUARY	9-11		
Y	US, A, 4,956,822 (BARBER ET Asee entire document.	AL.) 11 September 1990,	9-11		
Furth	ner documents are listed in the continuation of Box C	See patent family annex.			
• Sp	ecial categories of cited documents:	"T" later document published after the inte date and not in conflict with the applica			
	cument defining the general state of the art which is not considered be of particular relevance	principle or theory underlying the inve			
	rlier document published on or after the international filing date	"X" document of particular relevance; the considered novel or cannot be consider when the document is taken alone	e claimed invention cannot be red to involve an inventive step		
	ed to establish the publication date of another citation or other ecial reason (as specified)	"Y" document of particular relevance; the			
	cument referring to an oral disclosure, use, exhibition or other	considered to involve an inventive combined with one or more other such being obvious to a person skilled in th	documents, such combination		
*P" document published prior to the international filing date but later than the priority date claimed		*&* document member of the same patent family			
Date of the actual completion of the international search  Date of mailing of the international search report			rch report		
09 ОСТОВЕК 1996 2 8 FEB 1997					
Commissioner of Patents and Trademarks		Authorized officer			
Box PCT Washington, D.C. 20231 IAN J. LOBO					
Facsimile N	o. (703) 305-3230	Telephone No. (703) 306-4161	$(I \cup I \cup I)$		

AND PAGE BLANK (USPTO)